



The fact that these clamps are used on very small-bore hoses means that the material of the tube or hose can sometimes be very flexible, making it more difficult to ensure a leaktight assembly due to the possible deformation of the hose. In these cases, the inner-ring is key in helping to guarantee leaktightness as well as protecting the hose from being pinched during assembly.

MATERIAL: Clamp: Steel DC04 (EN 10130)

Inner-ring: Stainless steel AISI 301 1.4310 (10151)

FINISH: Clamp: Zinc plated Cr3

CORROSION RESISTANCE: Clamp: 72 hours salt spray (ASTM B-117)

Inner-ring: 250 hours salt spray (ASTM B-117)

| Ø Application | Part Number | A ±0.2 | B ±0.2 | C ±0.2 | D +0.5-0.2 | F ±0.2 | G ±0.2 | E +0.1-0.02 | Box Quantity | Outer Box Quantity |
|---------------|-------------|-----------|-----------|-----------|---------------|-----------|-----------|----------------|-----------------|-----------------------|
| 7.5-8.5 | 03011009 | 9,3 | 5,5 | 6,0 | 13,0 | 8,8 | 7,8 | 0,8 | 1.000 | 8.000 |
| 8.0-9.5 | 03011010 | 10,3 | 6,0 | 6,0 | 14,0 | 9,8 | 7,8 | 0,8 | 1.000 | 8.000 |
| 9.0-10.5 | 03011029 | 11,3 | 6,5 | 6,5 | 15,0 | 10,8 | 7,8 | 0,8 | 1.000 | 8.000 |
| 10.0-11.5 | 03011037 | 12,3 | 7,0 | 6,5 | 16,0 | 11,8 | 7,8 | 0,8 | 500 | 8.000 |
| 10.55-12.5 | 03011045 | 13,3 | 7,5 | 6,5 | 17,0 | 12,8 | 7,8 | 0,9 | 500 | 8.000 |
| 11.5-13.3 | 03011053 | 14,3 | 8,0 | 7,0 | 18,5 | 13,8 | 8,8 | 1,0 | 500 | 2.000 |
| 13.0-15.3 | 03011061 | 16,3 | 8,5 | 7,0 | 20,5 | 15,8 | 8,8 | 1,1 | 500 | 4.000 |
| 15.0-17.3 | 03011070 | 18,5 | 9,5 | 7,0 | 23,0 | 18,0 | 8,8 | 1,1 | 500 | 2.000 |